Now at your dealer or **wh.com**



Reliable. Efficient. Precise.

Turbines







Long service life and extremely quiet operation

Discover the new Alegra turbines with extremely quiet operation for daily use in your practice. Designed to meet your needs with state-of-theart technology. Made in Austria: For your best treatment results.

Up to the minute

W&H is a dynamic and rapidly expanding company. We guarantee

reliable support and outstanding

service. Our recipe for success:

quality material concepts, stringent

quality criteria and many years of

experience in the development of precision dental instruments.

innovative technologies, high



Long service life

Ceramic ball bearings guarantee minimum wear. Particularly with optimum care and maintenance!

Made in

AUSTRIA




Quiet

Alegra turbines offer top quality, vibration-free, quiet operation thanks to precision manufacture.



Replaceable water filter

Prevents dirt particles from entering the turbine.



Your reliable partner

This combination makes W&H turbines a reliable partner when working on your patients.








Maximum efficiency and safety during treatment

The Alegra range of turbines offers high-end technology for top preparation results! Experience maximum efficiency during use combined with maximum safety: for you and your patients.



Full steam ahead with the Power Blade rotor The optimized blade geometry allows higher rotor efficiency. For maximum torque and optimal power throughout preparation.



Precision cooling
The triple spray during treatment cools the treatment site from all sides and guarantees safety during treatment.



Tailor-made turbines
From hard-to-reach areas
to fast removal of tooth
structure: The right head size
for every application.



Patented hygienic head system

The circulating air in the turbine head ensures no aerosol particles are sucked into the turbine as the rotor slows down.




Hygiene & maintenance of your turbines

"The better the care, the longer the pleasure." Regular cleaning and care of your instruments protects them against premature wear and unnecessary service costs.



Short lubrication intervals -

long service life



Optimal view

and independent LED

The integration of a generator in the Roto Quick quick coupling gives you a low-cost option of adding an LED turbine to your selection of Alegra turbines. The advantages for you: Flexibility in use and in hygienic preparation.



Excellent ergonomics

Fatigue-free working thanks to easy 360° rotation of the turbine on the coupling, low overall weight and slender design.



LED turbine + quick coupling with generator = independent light

A generator in the Roto Quick quick coupling enables the use of light turbines on the turbine hose without a power supply.



Perfect for manual lubrication

W&H Service Oil F1 in the spray can cleans and lubricates your turbines to guarantee troublefree use.



Maintenance at the press of a button

The range of W&H maintenance units offers you optimal lubrication for your turbines. And all in record time!

Further advantages at a glance

- Integrated resuction stop: Prevents resuction of aerosol particles into the spray channel
- › Component replacement on site by the user
- > Thermo washer disinfectable
- Sterilizable up to 135 °C
- , 12 months warranty



Optimal view

The position of the LED in the turbine head guarantees optimal view and illumination of the treatment site.

Pictures are for illustrative purposes only. Additional equipment and accessories shown are not included as standard.

20415 AEN Rev. 007 / 21.03.2024 Subject to alterations

Technical data



Turbines with LED: Couplings with generator: Turbines without light:	TE-97 LQ* RQ-53 / RQ-54 TE-97 / TE-97 RM / TE-97 BC	TE-98 LQ* RQ-53 / RQ-54 TE-98 / TE-98 RM / TE-98 BC	TE-95 RM / TE-95 BC
Light (LED version):	LED and generator –		
Head size:	Ø 10.4 mm	Ø 12.2 mm	
Power**:	16 W	18 W	
Speed (min ⁻¹):	$390,000 \pm 30,000$	$330,000 \pm 30,000$	
Rotary instruments:	FG bur, in acc. with ISO 1797-1, Ø 1.6 mm		
Max. working part diameter:	2 mm		
Max. length:	21 mm	25 mm	
Weight: Turbines with LED Couplings with generator Turbines without light	46 g 26 g / 20 g 46 g / 47 g / 47 g	48 g 26 g / 20 g 48 g / 50 g / 50 g	49 g / 49 g
Operating pressure:	2.2-2.8 bar (recommended: 2.5 bar) (32-40 PSI)		
Ball bearings:	Ceramic		Steel
Spray:	Triple		Single

- * TE-97 LQ and TE-98 LQ turbines with LED are intended for use with W&H RQ-53 and RQ-54 Roto Quick couplings only.
- ** Performance value applies at a rated pressure of 2.5 bar for turbines without light, of 2.8 bar for turbines with light and exhaust air pressure of max. 0.2 bar. When operating with the maximum permissible operating pressure of 2.8 bar, it is possible to reach 16 watt for TE-97, TE-97 RM, TE-97 BC and 18 watt for TE-98, TE-98 RM, TE-98 BC.

Attention: Not all products mentioned in this brochure are available in all countries. Please contact your local W&H representative for details.

Manufacturer:

W&H Dentalwerk Bürmoos GmbH Ignaz-Glaser-Straße 53, Postfach 1 5111 Bürmoos, Austria t +43 6274 6236-0 f +43 6274 6236-55 office@wh.com

wh.com